


Kaye Validator® Pressure Transducer

HIGH PRECISE SENSOR FOR AUTOCLAVES



International and European norms (EN285, EN554, ISO-17665) for the validation of pharmaceutical, biotechnology and medical devices require the proof of saturated steam conditions in autoclaves. To achieve that a high accurate - temperature compensated - Pressure Transducer is needed.

Kaye's Autoclave Pressure Transducer (KG-075) is designed to meet this requirement. In combination with the Kaye Validator AVS System, saturated steam conditions can now be validated along with temperature. The pressure transducer is accurate and easy to connect. The Validator AVS will supply the power

required without the need for any additional power supplies.

FEATURES

- Designed for the harsh environment applications such as steam sterilizers and SIP systems
- High performance pressure transducer, specified at full temperature range of autoclave
- Can be directly connected to 1.5 in triclover flange
- Full ISO-17025 traceable calibration over pressure and temperature range
- Ease of Use – wires directly to Kaye Validator with no additional wiring or power supplies required

SOFTWARE SUPPORT

The Kaye Validator Report provides EN554, HTM2010 and ISO-17665 compliant reports.

The user can create:

- Saturated Pressure and Temperature Graph Reports utilizing temperature and pressure actual data along side calculated saturated readings
- Automatic equilibration pass/fail determination
- Automatic Tb, Tb+3 limit determination based on temperature versus saturated temperature, or pressure versus saturated pressure



CALIBRATION

Pressure calibration performed at 23°C and 121°C

SPECIFICATIONS

Type	Absolute Pressure Transducer
Range	0 bar to 4 bar (59 psia) Absolute
Sensitivity	1V to 5V
Non-linearity & hysteresis	±0.2% combined
Temp. compensated range	110°C – 140°C
Accuracy	10mbar (0.147 psi) at 110°C – 140°C



Kaye representative contact:

Request a demo:

EUROPE, MIDDLE EAST, AFRICA AND ASIA

Amphenol Advanced Sensors Germany GmbH
Sinsheimer Strasse 6
D-75179 Pforzheim
T: +49 (0) 7231-14 335 0
F: +49 (0) 7231-14335 29
Email: kaye@amphenol-sensors.com

USA/AMERICAS

Amphenol Thermometrics, Inc.
967 Windfall Road
St. Marys, PA 15857
T: +1(814) 834-9140
F: +1(814) 781-7969
Email: kaye-us@amphenol-sensors.com

INDIA

Amphenol Interconnect India Pvt Ltd.
Plot no. 6, Survey No.64 | Software Units layout
MAHAVEER TECHNO PARK
Hitech City, Madhapur | Hyderabad,
Telangana – 500081 | T: +91 40 33147100
Email: kaye-india@amphenol-sensors.com

CHINA

Amphenol (Changzhou) Connector
Systems Co., Ltd, Building 10,
Jintong Industrial Park, No. 8 Xihu Road,
Wujin High-Tech Development Zone,
Changzhou, Jiangsu 213164
T: 0086-519-83055197



Warranty and disclaimer: The information mentioned on documents are based on our current tests, knowledge and experience. Because of the effect of possible influences in an application of the product, they do not exempt the user from their own tests, checks and trials. A guarantee of certain properties or a guarantee for the proper suitability of the product for a specific, especially permanent application can not be derived from our data. Liability is therefore excluded to that extent permitted by law. Any proprietary rights of third parties as well as existing laws and regulations must be observed by the recipient of the product on his own responsibility.

© 2023 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice. Other company names and product names used in this document are the registered trademarks or trademarks of their respective owners.